

IN THE CLAIMS

Please amend the claims as follows, substituting any amended claim(s) for the corresponding pending claim(s):

1. (currently amended) A device for processing content data, the device comprises:
data processing circuitry operably coupled to process data received from an external content display device, wherein the data processing circuitry produces presentation information from the received data, the data processing circuitry includes:
parsing module operably coupled to receive the data, wherein the parsing module separates the data into the remote control data and the digitized audio;
remote control circuitry for process the remote control data to produce content presentation information, wherein the remote control circuitry provides the content presentation information to the content processing module, and wherein the content processing module processes the content data based on the content presentation information; and
signal processing module operably coupled to process the digitized audio, wherein the digitized audio is representative of audio signals received via a microphone of the external content display device;
content processing module operably coupled to process content data based on the presentation information for presentation on the external content display device; and
transceiving module operably coupled to the data processing circuitry and the content processing module, wherein the transceiving module separates modulated data from the content data and retrieves the received data from the modulated data of the external content display device, and wherein the transceiving module introduces the content data into a channel coupling the device to the external content display device.
2. (original) The device of claim 1, wherein the content data comprises at least one of: audio data, video data, text data, and multimedia data.
3. (original) The device of claim 1, wherein the data comprises at least one of: digitized audio, digitized video, and incoming remote control data.

4. (original) The device of claim 3, wherein the remote control data comprises at least one of:
volume adjust data, stop data, play data, pause data, rewind data, fast forward data, next track data,
channel up/down data, bass boost data, record data, intensity data, contrast data, security access data, and
telephone access code data.

5. (cancelled)

6. (original) The device of claim 1, wherein the transceiving module comprises:
high pass filter to separate the content data from the modulated data;
gain module operably coupled to provide gain to the modulated data to produce gained modulated
data; and
data extraction circuit operably coupled to retrieve the data from the gain modulated data.

7. (original) The device of claim 6, wherein the data extraction circuit comprises:
demodulator operably coupled to receive the gain modulated data and to produce therefrom
demodulated data;
quantizer operably coupled to receive the demodulated data and to produce therefrom quantized
data; and
digital filter operably coupled to receive the quantized data and produce therefrom the data.

8. (original) The device of claim 6, wherein the data extraction circuit comprises:
clock recovery circuit operably coupled to generate a clock signal from the gain modulated data;
a correlator operably coupled to receive the clock signal, wherein the correlator detect patterns of
the data contained within the modulated data to produce correlated data; and
phase comparator operably coupled to receive the correlated data and to produce therefrom the
data.

9. (original) The device of claim 1, wherein the data processing circuitry further comprises:
display information module operably coupled to provide outgoing display data to the transceiving
module.

- 1 10. (original) The device of claim 9, wherein the transceiving module further comprises:
2 data modulator operably coupled to modulate the outgoing display data to produce modulated
3 outgoing display data; and
4 combining circuit operably coupled to combine the content data and the modulated display data to
5 produce transmit data that is provided to the external content display device.
- 1 11. (original) The device of claim 10, wherein the data modulator comprises:
2 pseudo random code generator operably coupled to produce a random code; and
3 modulator operably coupled to receive the random code and the outgoing display data to produce
4 the modulated display data.
- 1 12. (original) The device of claim 10, wherein the combining circuit comprises:
2 high pass filter operably coupled to the channel, wherein the high pass filter filters the modulated
3 display data to produce filtered data, wherein the filtered data is provided on the channel; and
4 high frequency isolation module operably coupled to the channel, wherein the high frequency
5 isolation module substantially attenuates the filtered data and passes the content data substantially
6 untenanted such that the content data is isolated from the modulated display data.
- 1 13. (original) The device of claim 1 further comprises:
2 an external content display device detection module operably coupled to detect capabilities of the
3 external content display device in preparing the data.

Claims 14-32. - (Cancelled)

1 33. (currently amended) A device for processing content data, the device comprises:
2 a processing module; and
3 memory operably coupled to the processing module, wherein the memory includes operational
4 instructions that cause the processing module to:
5 receive modulated data via a channel coupled to an external content display device;
6 introduce the content data into the channel coupling the device to the external content
7 display device;
8 separate the modulated data from the content data by:
9 high pass filtering the channel to separate the content data from the modulated
10 data;
11 providing gain to the modulated data to produce gained modulated data; and
12 extracting the data from the modulated data by:
13 demodulating the gain modulated data to produce demodulated data;
14 quantizing the demodulated data to produce quantized data; and
15 digital filtering the quantized data to produce the data;
16 retrieve data from the modulated data;
17 process the data to produce processed data to produce presentation information; and
18 process content data for presentation on the external content display device based on the
19 presentation information.

1 34. (original) The device of claim 33, wherein the data includes at least one of: digitized audio,
2 digitized video, and incoming remote control data, wherein the memory further comprises operational
3 instructions that cause the processing module to:
4 parse the data into the remote control data and the digitized audio;
5 process the remote control data to produce content presentation codes;
6 process the content data based on the content presentation codes; and
7 process the digitized audio, wherein the digitized audio is representative of audio signals received
8 via a microphone of the external content display device.

Claims 35 – 37 (cancelled)

1 38. (original) The device of claim 33, wherein the memory further comprises operational instructions
2 that cause the processing module to:
3 modulate display data to produce modulated display data; and
4 combine the content data and the modulated display data to produce transmit data that is provided
5 to the external content display device.

1 39. (original) The device of claim 38, wherein the memory further comprises operational instructions
2 that cause the processing module to modulate the display data by:
3 generating a pseudo random code; and
4 modulating the pseudo random code and the display data to produce the modulated display data.

1 40. (original) The device of claim 38, wherein the memory further comprises operational instructions
2 that cause the processing module to modulate the display data by:
3 high pass filtering the transmit modulated display data to produce filtered data, wherein the
4 filtered data is provided on the channel; and
5 high frequency isolating the content data from the modulated display data by substantially
6 attenuating the filtered data and passing the content data substantially untenantated.

1 41. (original) The device of claim 33, wherein the memory further comprises operational instructions
2 that cause the processing module to:
3 detecting capabilities of the external content display device in preparing the data.

Claims 42-46 (Cancelled)

1 47. (New) A device for processing content data, the device comprises:
2 data processing circuitry operably coupled to process data received from an external content
3 display device, wherein the data processing circuitry produces presentation information from the received
4 data;
5 content processing module operably coupled to process content data based on the presentation
6 information for presentation on the external content display device; and
7 transceiving module operably coupled to the data processing circuitry and the content processing
8 module, wherein the transceiving module separates modulated data from the content data and retrieves the
9 received data from the modulated data of the external content display device, and wherein the
10 transceiving module introduces the content data into a channel coupling the device to the external content
11 display device, the transceiving module includes:
12 high pass filter to separate the content data from the modulated data;
13 gain module operably coupled to provide gain to the modulated data to produce gained
14 modulated data; and
15 data extraction circuit operably coupled to retrieve the data from the gain modulated data,
16 wherein the data extraction circuit includes:
17 demodulator operably coupled to receive the gain modulated data and to
18 produce therefrom demodulated data;
19 quantizer operably coupled to receive the demodulated data and to
20 produce therefrom quantized data; and
21 digital filter operably coupled to receive the quantized data and produce
22 therefrom the data.

1 48. (New) The device of claim 47, wherein the content data comprises at least one of: audio data,
2 video data, text data, and multimedia data.

1 49. (New) The device of claim 47, wherein the data comprises at least one of: digitized audio,
2 digitized video, and incoming remote control data.

1 50. (New) The device of claim 49, wherein the remote control data comprises at least one of: volume
2 adjust data, stop data, play data, pause data, rewind data, fast forward data, next track data, channel
3 up/down data, bass boost data, record data, intensity data, contrast data, security access data, and
4 telephone access code data.

1 51. (New) The device of claim 49, wherein the data processing circuitry comprises:
2 parsing module operably coupled to receive the data, wherein the parsing module separates the
3 data into the remote control data and the digitized audio;
4 remote control circuitry for process the remote control data to produce content presentation
5 information, wherein the remote control circuitry provides the content presentation information to the
6 content processing module, and wherein the content processing module processes the content data based
7 on the content presentation information; and
8 signal processing module operably coupled to process the digitized audio, wherein the digitized
9 audio is representative of audio signals received via a microphone of the external content display device.

1 52. (New) The device of claim 47, wherein the data processing circuitry further comprises:
2 display information module operably coupled to provide outgoing display data to the transceiving
3 module.

1 53. (New) The device of claim 52, wherein the transceiving module further comprises:
2 data modulator operably coupled to modulate the outgoing display data to produce modulated
3 outgoing display data; and
4 combining circuit operably coupled to combine the content data and the modulated display data to
5 produce transmit data that is provided to the external content display device.

1 54. (New) The device of claim 53, wherein the data modulator comprises:
2 pseudo random code generator operably coupled to produce a random code; and
3 modulator operably coupled to receive the random code and the outgoing display data to produce
4 the modulated display data.

1 55. (New) The device of claim 53, wherein the combining circuit comprises:
2 high pass filter operably coupled to the channel, wherein the high pass filter filters the modulated
3 display data to produce filtered data, wherein the filtered data is provided on the channel; and
4 high frequency isolation module operably coupled to the channel, wherein the high frequency
5 isolation module substantially attenuates the filtered data and passes the content data substantially
6 untenantated such that the content data is isolated from the modulated display data.

- 1 56. (New) The device of claim 47 further comprises:
2 an external content display device detection module operably coupled to detect capabilities of the
3 external content display device in preparing the data.